

SPACIO

—By Sigfrido Bilbao—



DESCRIPTION

Polypropylene (P.P) back with 15% fiberglass. Wide range of colours. Optional Polypropylene (P.P) Arms reinforced with fibre glass.

Anti-skid surface Seat:

- shell, moulded Polypropylene (P.P)
- Upholstered over foam (40-45kg/m³).

Frame manufactured with carbon cold-rolled steel 28x20x1,5mm thickness. Silver epoxy coat, 90 micron and anti-bacterial treatment. Stacking caps included.

BACK AND SEAT



(SEE FINISHES AND FABRIC CARD LAST PAGE)

COMPLEMENTS



Optional Hook on basket Ø 5 mm thickness with supports Ø 7 mm thickness. **Aluminum finish**



Optional writing tablet, compact laminate 13 mm. It could be fixed to the right or left hand side



Polypropylene (P.P) linking devices 5 mm thickness


SIZES

Total height: 830 mm
Total width: 500 mm
Total depth: 530 mm

Seat height: 420 mm
Seat width: 470 mm
Seat depth: 440 mm



- ① Polypropylene (P.P) 5 mm thickness with fiberglass backrest. Ergonomic shaped back including transpiration strips
- ② **Optional** arms: Polypropylene (P.P) with fiberglass
- ③ Back reinforcement
- ④ Anti-skid surface seat
- ⑤ Stacking caps
- ⑥ Steel tube frame, **silver finish**
- ⑦ Polypropylene (P.P) glides and caps, matching seat and backrest



DESCRIPTION

Polypropylene (P.P) back with 15% fiberglass.

Wide range of colours. Optional Polypropylene (P.P).

Arms reinforced with fibre glass.

Anti-skid surface Seat:

-shell, moulded Polypropylene (P.P)

-Upholstered over foam (40-45kg/m³).

Silver epoxy coat, 90 micron and anti-bacterial treatment. Black or silver polyamide (PAG + 30% FV) start. Base Ø 65 cm with black or dark grey castors. Gas lift.

BACK AND SEAT



(SEE FINISHES AND FABRIC CARD LAST PAGE)

BASES AND CASTORS



Black Polyamide - Ø 65 cm
Black Polyamide castor Ø 50 mm
Black anti-skid castor Ø 50 mm



Dark grey Polyamide - Ø 65 cm
Dark grey Polyamide castor Ø 50 mm
Dark grey anti-skid castor Ø 50 mm

SIZES

Total height: from 850 to 955 mm

Total width: 650 mm

Total depth: 650 mm


Seat height: 420 mm

Seat width: 470 mm

Seat depth: 440 mm



- ① Polypropylene **(P.P)** 5 mm thickness with fibre glass backrest. Ergonomic shaped back including transpiration strips
- ② Back reinforcement
- ③ **Optional** arms: Polypropylene **(P.P)** with fiberglass
- ④ Anti-skid surface seat
- ⑤ Gas lift
- ⑥ Base Ø 65 cm **(PAG+30% FV)**
- ⑦ Anti-skid castors Ø 50 mm



DESCRIPTION

Polypropylene (P.P) back with 15% fiberglass.

Wide range of colours. Optional Polypropylene (P.P) Arms reinforced with fibre glass.

Anti-skid surface Seat:

-shell, moulded Polypropylene (P.P)

-Upholstered over foam (40-45kg/m³).

Chromed steel footrest. Curved tube Ø 18 x 1,5 mm thickness. Swivel 5 star base Ø 67,5 cm available in Silver aluminium or black polyamid with Polypropylene (P.P) black caps. Gas lift.

BACK AND SEAT



(SEE FINISHES AND FABRIC CARD LAST PAGE)

BASE



Swivel silver aluminum base - 67,5 cm
Polypropylene (PP) black caps



Swivel black polyamide base - 67,5 cm
Polypropylene (PP) black caps

SIZES

Total height: from 1050 mm to 1230 mm

Total width: 675 mm

Total depth: 206 mm


Seat height: 420 mm

Seat width: 470 mm

Seat depth: 440 mm



- ① Polypropylene (P.P) 5 mm thickness with fiberglass backrest. Ergonomic shaped back including transpiration strips
- ② Back reinforcement
- ③ **Optional** arms: Polypropylene (P.P) with fiberglass
- ④ Anti-skid surface seat
- ⑤ Gas lift
- ⑥ Chromed steel footrest. Curved tube Ø 18 x 1,5 mm thickness
- ⑦ 5 Star base, Ø 67,5 cm finished in **Silver aluminium or black polyamide**
- ⑧ Polypropylene (P.P) black caps





DESCRIPTION

- ① Polypropylene (P.P) back with 15% fiberglass. Wide range of colours. Optional Polypropylene (P.P). Arms reinforced with fiberglass.
- ② Back reinforcement.
- ③ Anti-skid surface Seat: shell, moulded Polypropylene (P.P).
- ④ Steel legs, cone shape 35 x 40 and 1,5 mm thickness. Silver epoxy coat, 90 micron and anti-bacterial treatment.
- ⑤ Moulded steel beam. Silver finish 80 x 40 and 2 mm thickness.
- ⑥ Moulded ABS leveler. Polyethylene (PE) caps Ø 40 mm.
- ⑦ Optional MFC table in different finishes: elm, walnut. 4 and 5 seats SPACIO beams include a central support leg.

BACK AND SEAT




[SEE FINISHES AND FABRIC CARD LAST PAGE]

SIZES

Total height: 830 mm
Total width: from 1150 mm to 2380 mm
Total depth: 590 mm

Seat height: 420 mm
Seat width: 470 mm
Seat depth: 440 mm





MATERIALS

Maximum use of materials to eliminate and minimize scraps. Use of recyclable and recycled materials in those components that do not affect the functionality and durability.

8,53%
RECYCLED
MATERIALS



PRODUCTION

Maximum optimization of energy use. Minimal environmental impact. Last generation technological systems. Zero discharge of wastewater. No VOC coatings. Processes free of heavy metals, phosphates, OC and COD.

100%
RECYCLABLE
ALUMINIUM, STEEL
& WOOD



TRANSPORT

Detachable systems. Volumes that facilitate the optimization of space. Maximum reduction of energy consumption by transport.

100%
RECYCLABLE
PACKAGE AND THINNER
FREE



USE

Quality and warranty. Long lasting. Replacements available.

EASY
TO CLEAN
AND MAINTAIN



DISPOSAL

Waste reduction. Supplier-manufacturer packaging reuse system. Components are easy to be separated. Inks in packaging are water-based, without solvents.

98,99%
RECYCLABLE
MATERIALS

CERTIFICATES AND REFERENCES

The different programmes get points in different environmental categories to get the LEED certificate (sustainability, material and resources, water, energy and atmosphere, inner environment quality, innovation and design).



The mark of
responsible forestry



PEFC Certificate



EN ISO 14006:2011
ECODESIGN Certificate



UNE-EN ISO 9001:2008
ISO 9001 Certificate



UNE-EN ISO 14001:2004
ISO 14001 Certificate



E1 Certificate
by EN 13986



ACTIU TECHNOLOGY PARK
LEED® PLATINUM certified by USGBC
Leadership in Energy & Environmental Design
LEED® Gold certified 2011 - LEED® Platinum certified 2017

STANDARDS

SPACIO has passed tests done in our technical department as well as the tests done in **AIDIMA** the Technological Institute for furniture.

The tests correspond to:

Confident office chair. Standard applied

- **UNE-EN 13761:04.** Office furniture. Confident chairs.
- **UNE-EN 1022:05.** Office furniture. Confident chairs.
- **UNE-EN 1728:00.** Domestic furniture - Seating - Test methods for the determination of strength and durability.


Gas Lift. Standard applied

- **UNE-EN 1335-1:01.** Office Furniture. Office chair. Part 1: Dimensions.
- **UNE-EN 1335-3:09.** Office Furniture. Office chair. Part 3: Security essays.


Beam Seating. Standard applied

- **UNE-EN 16139:13.** Furniture. Resistance, long lasting, security. Requirements for non domestic use seating.

■ 4 LEGGED CHAIR WITH WRITING TABLET



With weight more than 15 kg.
Without a seated user, the chair overturns.



With a seated user, maximum
resistance of writing tablet 40 kg.

FABRIC

■ BACK & SEAT



Moulded polypropylene (P.P)

POLYPROPYLENE




■ BACK



Upholstered over foam (40-45kg/m³),
Fabric T or Fabric N

Fabric T - Newport



Fabric V - Valencia

