

sirena seating | product specification

Sirena Lounge Seating Models 3371, 3372, 3373 & 3374

Dimensions

Overall Depth	29.5 in / 749 mm
Overall Height	28.5 in / 724 mm
Seat Depth	20 in / 508 mm
Seat Height	17.5 in / 445 mm
Arm Height - From Seat	9.5 in / 241 mm

Single Chair (Models 3371 & 3372)

Overall Width	30.5 in / 775 mm
Seat Width	20.0 in / 508 mm
Armrest Clearance	20.0 in / 508 mm
Product Weight	3371 45 lbs / 20.5 kgs
	3372 47 lbs / 21.4 kgs
Shipping Weight	3371 52 lbs / 23.6 kgs
	3372 55 lbs / 25.0 kgs
Shipping Cube	19.25 ft ³ / 0.54 m ³

Two Seat Sofa (Model 3373)

Overall Width	62.0 in / 1575 mm
Seat Width	53.0 in / 1346 mm
Armrest Clearance	53.0 in / 1346 mm
Product Weight	82 lbs / 37.3 kgs
Shipping Weight	92 lbs / 41.8 kgs
Shipping Cube	48.0 ft ³ / 1.36 m ³

Three Seat Sofa (Model 3374)

Overall Width	81.5 in / 2070 mm
Seat Width	72.5 in / 1842 mm
Armrest Clearance	72.5 in / 1842 mm
Product Weight	97 lbs / 44.1 kgs
Shipping Weight	107 lbs / 48.6 kgs
Shipping Cube	55.5 ft ³ / 1.57 m ³

Contact sales rep for more information.



3371



5472-CP (contrasting piping)



3372 (MDF shelf)



3372RTM (casters and MDF shelf)



3373



3374



sirena seating | product specification

Features

- Fixed, non-removable seat cushion (for public areas)
- Certain models feature tablets and/or storage shelves under seat

Options

- Tablet arm can be applied to left or right arm of sofa MODELS 3371 & 3372
- Available with 4 casters instead of feet

On Site Repair and Replacement

- Glides are replaceable on site
- Table arms can be removed or replaced on site, but cannot be removed without special knowledge (for public spaces)

Construction (Arms & Back)

- Base constructed with 1 in (25 mm) thick plywood frame with interlocking construction features
- Zinc inserts provide metal to metal connections to other components to improve ease of on-site repair and prolong products life cycle
- Top of frame is sealed with a plywood top plate and structured to accept optional tablet arms
- Seat back is sealed with cardboard

Construction (Seat)

- Flexible webbed seat suspension system
- 1 in (25 mm) thick wooden inner seat frame
- Seat is fastened to curved chair back/sides with brackets
- Woven synthetic webbing under cushion

Construction (Glides or Casters)

- Standard with 4 black glides
- Optional casters:
 - 50 mm (2.0 in) hard (carpet) casters made of reinforced nylon or soft (hard surface) casters made of polyurethane coated nylon
 - Twin-wheeled

Construction (Shelves and Tablets)

- Shelves and tablets are made of a choice of laminate or epoxy finished MDF
- Tablets are 17 in (432 mm) wide, 14 in (356 mm) deep

Upholstery (Seat)

- Can be upholstered in fabric, vinyl, leather, or leather/mock leather
- Cushions are fixed to prevent removal (for public spaces)
- Fully upholstered sides and top
- Can be upholstered in fabric, vinyl, leather, or mock leather
- Underside of chair is sealed by fabric cover

Foam (Seat)

- Seat cushion is made of Ultracell Bio foam
- 2.75 in (70 mm) thick foam
- Density: 2.6 lbs, ILD: 35

Foam (Arms & Back)

- Back foam is 1.5 in (38 mm) thick foam
- Arm foam is 1 in (25 mm) thick
- Density: 1.5 lbs, ILD: 40

Weight Capacity

Designed for a static load of 1000 lbs and an active weight capacity of 300 lbs per seat

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foams and fabrics
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All fabric and foam is tested and certified, meeting CAL 117 standards.

Environmental

View [Environmental Data Sheets](#) online.

All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.

