

popcorn seating | product specification

Counter Stools

Models 6710CS, 6711CS, 6712CS & 6713CS

Barstools

Models 6710BS, 6711BS, 6712BS & 6713BS

Dimensions

Overall Depth		25.5 in / 648 mm
Overall Height	67##CS	40.5 in / 1029 mm
	67##BS	44.5 in / 1130 mm
Seat Depth		18 in / 457 mm
Seat Width		18 in / 457 mm
Seat Height	6710CS & 6711CS	24 in / 610 mm
	6712CS & 6713CS	24.5 in / 622 mm
	6710BS & 6711BS	29 in / 737 mm
	6712BS & 6713BS	29.5 in / 749 mm
Back Height - From Seat	6710__ & 6711__	16 in / 406 mm
	6712__ & 6713__	15.5 in / 394 mm

With Armrests (Models 6710CS, 6710BS, 6712CS & 6712BS)

Overall Width		24.5 in / 622 mm
Armrest Clearance		21 in / 533 mm
Arm Height - From Seat	6710__	8 in / 203 mm
	6712__	7.5 in / 191 mm
Product Weight	6710CS	20 lbs / 9.1 kg
	6710BS	25 lbs / 11.4 kg
	6712CS	22 lbs / 10 kg
	6712BS	27 lbs / 12.3 kg
Shipping Weight (Two per carton)	6710CS	48 lbs / 21.8 kg
	6710BS	58 lbs / 26.4 kg
	6712CS	52 lbs / 23.6 kg
	6712BS	60 lbs / 27.3 kg
Shipping Cube		21.5 ft ³ / 0.61 m ³

Without Armrests (Models 6711CS, 6711BS, 6713CS & 6713BS)

Overall Width		20 in / 508 mm
Product Weight	6711CS	18 lbs / 8.2 kg
	6711BS	23 lbs / 10.5 kg
	6713CS	20 lbs / 9.1 kg
	6713BS	25 lbs / 11.4 kg
Shipping Weight (Two per carton)	6711CS	44 lbs / 20 kg
	6711BS	54 lbs / 24.5 kg
	6713CS	48 lbs / 21.8 kg
	6713BS	56 lbs / 25.5 kg
Shipping Cube		17.5 ft ³ / 0.50 m ³

Contact sales representative for more information.



6710CS (counter stool)



6713CS (counter stool)



6711BS (barstool)



6712BS (barstool)



popcorn seating | product specification

Features

- Sled base
- Crossbar footrest
- Leg design prevents chair back from damaging walls
- Seat pan has waterfall edge to help maintain proper leg circulation
- Designed to be easily moved via a hand-hold pass through located on top edge of chair
- Seating shipped fully assembled
- Stacks up to eight high on floor

MODELS 6710BS, 6710CS, 6712BS & 6712CS

- Integrated arms match shell colour

Options

- Four glide options are available:
 - Clear polycarbonate glides are recommended for carpet, rubber or concrete flooring
 - Glides with stainless steel pads are recommended for carpet or rubber flooring
 - Glides with felt pads are recommended for vinyl, cork or laminate flooring
 - Glides with rubber pads are recommended for vinyl, hardwood, laminate, stone or ceramic flooring
- Chair shell available in 14 versatile colours: Buzz Blue, Cactus, Carrot, Cloud, Dijon, Eggplant, Fog, Frost, Ink, Latte, Night, Sand, Scarlet and Shadow
- Ganging clamps are available for linking chairs. No clearance between chairs with armrests. 5 in (127mm) clearance between chairs without armrests

Construction (Frame)

- Solid steel rod with chrome finish
- 0.5 in (13 mm) diameter

Construction (Seat and Back)

- Molded, single piece, polypropylene shell

Construction (Arms)

MODELS 6710BS, 6710CS, 6712BS & 6712CS

- Fiberglass reinforced cantilever nylon arms
- Cantilever design allows freedom of movement and accommodates larger users

Construction (Glides)

- Optional clear polycarbonate glides, with or without pads
- Polycarbonate glides are translucent and non-marking

Upholstery

MODELS 6712BS, 6712CS, 6713BS & 6713CS

- Seat can be upholstered in fabric, vinyl or leather
- Polypropylene shroud on underside of seat frame prevents imprints or damage to other chairs when stacked

Foam (Seat)

MODELS 6712 & 6713

- 0.75 in (19 mm) thick foam
- Density: 1.5 lbs ILD: 70

Weight Capacity

Designed for an active weight capacity of 300 lbs per seat

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foams and fabrics
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All fabric and foam is tested and certified, meeting California Technical Bulletin 117 (CAL 117) standards

Environmental

View [Environmental Data Sheets](#) online. All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.



popcorn seating | product specification

Glide Selections

Surface	Carpet	Vinyl Sheet	LVT	VCT	Rubber	Cork	Hardwood	Laminate	Ceramic, Tile, Stone	Marble, Granite	Concrete
No glide (XG) 	●	NR	NR	NR	●	NR	NR	NR	NR	NR	NR
Clear polycarbonate glide (CG) 	●	NR	NR	NR	●	NR	NR	NR	NR	NR	●
Stainless steel pad on polycarbonate glide (SG) 	●	NR	NR	NR	●	NR	NR	NR	NR	NR	NR
Felt pad on polycarbonate glide (FG) 	NR	●	●	NR	NR	●	NR	●	NR	NR	NR
Rubber no slip pad on polycarbonate glide (RG) 	NR	●	●	●	NR	NR	●	●	●	●	NR

Note The above is only a guideline based on clean and properly finished floors. Glides that are not recommended for use will not be covered by Global's lifetime warranty. Site conditions can dramatically affect how appropriate a glide is for any application. Regular inspection of glides is critical to preventing floor damage. See descriptions below.

- = Best for application
- NR = Not recommended for use

No glide (XG) The plain Chrome sled based frame slides easily and silently over carpeted surfaces. Note: do not use in damp areas.

Clear polycarbonate glide (CG) The polycarbonate glide is easy to move over most flooring. It does not leave marks and it reduces noise on hard surfaces.

Stainless steel pad on polycarbonate glide (SG) The stainless steel bottomed glide slides easily. It is extremely durable, reduces floor contact and noise on hard surfaces.

Felt pad on polycarbonate glide (FG) The felt bottomed glide moves silently and smoothly on hard surface flooring. Helps to prevent floor damage.

Rubber no slip pad on polycarbonate glide (RG) The rubber bottomed glide is slip-resistant. It grips flooring, reduces movement, scratching and eliminates noise.

